

From: Rand Crafts
To: Milka Radulovic
Date: Wed, Nov 19, 2003 1:51 PM
Subject: IPP Burner Replacement

Milka,

Info on the operational performance of current IPP burners is attached. Note that the data indicate the present burners are capable of 248 mmbtu/hr. Current burners are B&W Dual Register, Phase 5 burners, with a 58" throat.

The new burners will be Advanced Burner Technologies (ABT), Opti-Flow burners, with a 51" throat, design rated at 220 mmbtu/hr.

The heat input limitation prior to the dense pack project was due to the boiler and turbine capability. The heat input limitation is now due to the mills, B&W Model MPS89. The burners have never been a bottleneck, so replacement will not increase mmbtu/hr capacity of the boiler.

I believe this wraps up all the info you have requested. Please acknowledge and let me know what you think the timeline will be for publishing an ITA. Thanks.

Rand Crafts
Intermountain Power Service Corp
rand-c@ipsc.com
435-864-6494
435-864-0994 Fax

CONFIDENTIALITY NOTICE

This e-mail transmission, and any documents, files or previous e-mail messages attached to it may contain information that is confidential or legally privileged. If you are not the intended recipient, or a person responsible for delivering it to the intended recipient, you are hereby notified that you must not read this transmission and that any disclosure, copying, printing, distribution or use of any of the information contained in or attached to this transmission is STRICTLY PROHIBITED. If you have received this transmission in error, please immediately notify the sender by telephone or return e-mail and delete the original transmission and its attachments without reading or saving in any manner. Thank you.

CC: Blaine Ipson; James Nelson

Turbine Acceptance Test Results: Maximum Heat Input

Plant Info: 8 mills per unit
 6 burners per mill
 Normal Operating Mode: 7 mills
 High Performance Mode: 6 mills

| Unit 2 | | | | | | Total | Heat per burner |
|---------|--------|-------|--------|-----------|-------------|---------|-----------------|
| | Test # | MW | ton/hr | # pulv /s | PI HHV coal | Mbtu/hr | Mbtu/hr |
| 4/11/02 | 7 | 985.5 | 370.6 | 6 | 12,050 | 8931.46 | 248.10 |
| 4/11/02 | 8 | 982.6 | 370.5 | 8 | 12,050 | 8929.05 | 248.03 |
| 5/14/02 | 9 | 975.5 | 394.02 | 7 | 11,879 | 9361.13 | 222.88 |
| 5/14/02 | 10 | 973.1 | 392.64 | 7 | 11,879 | 9328.34 | 222.10 |

| Unit 1 | | | | | | Total | Heat per burner |
|---------|--------|-------|--------|-----------|-------------|---------|-----------------|
| | Test # | MW | ton/hr | # pulv /s | PI HHV coal | Mbtu/hr | Mbtu/hr |
| 4/17/03 | 8 | 979.6 | 388.8 | 7 | 11,877 | 9230.80 | 219.78 |
| 4/18/03 | 9 | 976.6 | 390.1 | 7 | 11,877 | 9266.44 | 220.63 |
| 5/29/03 | 10 | 969.3 | 380.1 | 7 | 11,730 | 8917.15 | 212.31 |
| 5/29/03 | 11 | 969.3 | 393.2 | 7 | 11,730 | 9224.47 | 219.63 |